



- Display:30x60mm LCD display 24mm
- Auto power off
- Size Weight::91X189X31.5mm 310g
- (including battery)
- Continuity checking with buzzer
- Power 6F22(9V) X1
- DC Voltage
- 200mV±1.2%, 2/20/200V±0.8%, 700V±1.2%
- AC Voltage
- 200m/2/20/200 V±0.5%, 1000V±0.8%
- DC Current
- 2m/20mA±0.8%, 200mA±1.5%, 10A±2%
- AC Current
- 2m/20mA±1.0%, 200mA±1.8%, 10A±3%
- Resistance
- 200/2k/20k/200k/2M Ω ±0.8%, 20M Ω ±1.0%, 200M Ω ±5%
- Capacitance
- 2n/20n/200n/2 μ /20 μ F±4.0%
- Diode check
- Test current 1.0mA, Test Voltage 2.8V
- hFE
- 1~1000



**MY60T**

- 32 ranges
- Large LCD display
- Auto power off
- DC Voltage:200m/2/20/200V±0.5%, 1000V±0.8%
- AC Voltage: 200m V±1.2%, 2/20/200V±0.8%, 700V±1.2%
- DC Current: 20 μ A±2%, 200 μ /2m/20mA±0.8%, 200m/2A±1.5%, 10A±2%
- AC Current: 200m/2A±1.8%, 2m/20mA±1.0%, 10A±3%
- Resistance : 200/2k/20k/200k/2M Ω ±0.8%, 20M Ω ±1.0%, 200M Ω ±5%
- Temperature:-20℃~1000℃
- Continuity checking with buzzer
- Diode check:Test current 1.0mA, Test Voltage 2.8V
- hFE:1~1000
- Power 6F22(9V) X1
- Size Weight::91X189X31.5mm 310g
- (including battery)
- Display:30x60mm LCD

**New M 92 A**

- 32 ranges
- Large LCD display
- Auto power off
- DC Voltage:200m/2/20/200V±0.5%, 1000V±0.8%
- AC Voltage: 200m V±1.2%, 2/20/200V±0.8%, 700V±1.2%
- DC Current: 20 μ A±2%, 200 μ /2m/20mA±0.8%, 200m/2A±1.5%, 10A±2%
- AC Current: 200 μ /200m/2A±1.8%, 2m/20mA±1.0%, 10A±3%
- Resistance : 200/2k/20k/200k/2M Ω ±0.8%, 20M Ω ±1.0%, 200M Ω ±5%
- Continuity checking with buzzer
- Diode check:Test current 1.0mA, Test Voltage 2.8V
- hFE:1~1000
- Power 6F22(9V) X1
- Size Weight::91X189X31.5mm 310g
- (including battery)
- Display:30x60mm LCD

